

Specification Compliance Table

Dispatch Console furniture

Appendix D

Please note: An indication of compliance (Y) means that the Vendor accepts responsibility for, and agrees to comply with, the requirement as stated; any additional comments in the explanation column will be ignored. Partial compliance will be indicated with a (P), Non-compliance will be indicated with an (N) and both must be accompanied by a detailed explanation

Specification Section	Compliance Y / P / N	Comment / Explanation
3.1.1 - Flexibility / Function		
3.1.1.1		
3.1.1.2		
3.1.1.3		
3.1.1.4		State value: <u>360</u> (Spec requires 300 lbs.)
3.1.1.5		
3.1.1.6		
3.1.1.7		
3.1.2 – Keyboard Surface – Sitting/Standing		
3.1.2.1		State value: <u>500</u> (Spec requires 500lbs.)
3.1.2.2		State height <u>23"</u> (Spec requires 23")
3.1.2.3		State height <u>50"</u> (Spec requires 46.7")
3.1.2.4		
3.1.2.5		
3.1.3 – Monitor Surface – Sitting/Standing		
3.1.3.1		
3.1.3.2		Requires submittal of dimensioned drawings detailing how specified monitor view angles are achieved
3.1.3.3		
3.1.3.4		
3.1.3.5		
3.1.4 – Adjustment Devices		
3.1.4.1		
3.1.4.2		
3.1.4.3		
3.1.4.4		
3.1.4.5		State speed: <u>1.4"</u> (Spec requires 1.4" / second)
3.1.4.6		
3.1.4.7		
3.1.4.8		State min. clearance: <u>1"</u> (Spec requires 1")
3.1.4.9		
3.1.4.10		
3.1.4.11		Collision detection works in both directions <u>Y</u> Y/N Collision detection works on both surfaces <u>Y</u> Y/N Collision detection works regardless of location of obstruction <u>Y</u> Y/N
3.1.5 – Computerized Adjustment Software		
3.1.5.1		
3.1.5.2		
3.1.5.3		
3.1.5.4		
3.1.5.5		
3.1.5.6		

Specification Section	Compliance Y / P / N	Comment / Explanation
3.1.5.7		
		3.1.6 – Laminate – Console Tops and Side Surfaces
3.1.6.1		State thickness __.048”__ (Spec requires min. 048” thickness)
3.1.6.2		
3.1.6.3		State radii __3”__ (Spec requires 3” corners - .4375” top edge)
3.1.6.4		
3.1.6.5		
3.1.6.6		
		3.1.7 – Laminate – CPU Cabinets, Drawer Pedestals and other casework
3.1.7.1		
3.1.7.2		
		3.1.8 – Knee space / Legroom
3.1.8.1		
3.1.8.2		ANSI/HFES 100-2007 Requirement 23.6” Desired depth 31” State depth at level of foot _____
		3.1.9 – Mobile Drawer Pedestal
3.1.9.1		
3.1.9.2		
3.1.9.3		
3.1.9.4		
3.1.9.5		
		3.1.10 – Segmented Panel System
3.1.10.1		
3.1.10.2		
3.1.10.3		
3.1.10.4		
3.1.10.5		
3.1.10.6		
3.1.10.7		
3.1.10.8		
3.1.10.9		
3.1.10.10		
3.1.10.11		
3.1.10.12		
3.1.10.13		Panel Frames manufactured completely with Non-Combustible Materials Y or N
3.1.10.14		
3.1.10.15		
		3.1.11 – Shelving and Rackmount Enclosures
3.1.11.1		
3.1.11.2		
3.1.11.3		
		3.1.12 – Cable Management
3.1.12.1		
3.1.12.2		
3.1.12.3		
3.1.12.4		
3.1.12.5		
3.1.12.6		
3.1.12.7		
		3.1.13 – CPU Enclosures
3.1.13.1		

Specification Section	Compliance Y / P / N	Comment / Explanation
3.1.13.2		
3.1.13.3		
3.1.13.4		
3.1.13.5		
3.1.13.6		
3.1.13.7		
3.1.13.8		
3.1.13.9		
3.1.13.10		
3.1.13.11		
		3.1.14 Optional Console Anchoring
3.1.14.1		
3.1.14.2		
3.1.14.3		
3.1.14.4		
		3.1.15 Rotating Resource Guide
3.1.15.1		
3.1.15.2		
3.1.15.3		
3.1.15.4		
3.1.15.5		
3.1.15.6		
3.1.15.7		
		3.1.16 Personal Climate Controls
3.1.16.1		
3.1.16.2		
3.1.16.3		
3.1.16.4		
3.1.16.5		
3.1.16.6		
3.1.16.7		
3.1.16.8		
		3.1.17 Adjustable Monitor Rack
3.1.17.1		
3.1.17.2		
3.1.17.3		
3.1.17.4		
3.1.17.5		
3.1.17.6		
3.1.17.8		
3.1.17.9		
3.1.17.10		
3.1.17.11		
3.1.17.12		
		3.1.18 Keyboard Surface Data Connection (KSDCC)
3.1.18.1		
3.1.18.2		
3.1.18.3		
3.1.18.4		
		3.1.19 Environmental
3.1.19.1		
3.1.19.2		
		3.1.20 Manufacturing Lead Times

Specification Section	Compliance Y / P / N	Comment / Explanation
3.1.20.1		Number of days to manufacture and deliver to job site _____

Attach the following certificates of Standard Compliance. (Only 3rd party laboratory testing is acceptable)

1. BIFMA – X 5.9-2004 – Drawer Pedestals
2. BIFMA – X5.5 ?? – Adjustable Tables
3. BIFMA – X5.3-2003 – Panel Enclosure System
4. GreenGuard Certification
5. Acoustical NRC test results